

# **Device Modeling Report**

**COMPONENTS:**

DIODE/ SCHOTTKY RECTIFIER / STANDARD

PART NUMBER: 1SS349

MANUFACTURER: TOSHIBA




**Bee Technologies Inc.**


PSpice model parameter	Model description
IS	Saturation Current
N	Emission Coefficient
RS	Series Resistance
IKF	High-injection Knee Current
CJO	Zero-bias Junction Capacitance
M	Junction Grading Coefficient
VJ	Junction Potential
ISR	Recombination Current Saturation Value
BV	Reverse Breakdown Voltage(a positive value)
IBV	Reverse Breakdown Current(a positive value)
TT	Transit Time
EG	Energy-band Gap

## Forward Current Characteristic

Circuit Simulation Result




Evaluation Circuit



## Comparison Graph

Circuit Simulation Result




Simulation Result


$I_{fwd}$ (A)	$V_{fwd}$ (V) Measurement	$V_{fwd}$ (V) Simulation	%Error
0.1	0.220	0.216	-1.73
0.2	0.234	0.234	0.04
0.5	0.260	0.258	-0.85
1	0.275	0.276	0.25
2	0.292	0.294	0.58
5	0.317	0.318	0.25
10	0.335	0.336	0.15
20	0.353	0.354	0.20
50	0.377	0.378	0.29
100	0.395	0.397	0.56

## Junction Capacitance Characteristic

### Circuit Simulation Result




### Evaluation Circuit



## Comparison Graph

### Circuit Simulation Result



### Simulation Result

$V_{rev}$ (V)	$C_j$ (pF) Measurement	$C_j$ (pF) Simulation	%Error
0.1	243.00	242.80	-0.08
0.2	224.00	224.50	0.22
0.5	188.00	187.70	-0.16
1	154.00	153.60	-0.26
2	120.00	119.40	-0.50
5	81.00	81.70	0.86
10	59.50	59.70	0.34
20	44.00	43.31	-1.57